TOSHIBA

BV410D BV420D

Desktop printer series

Product brochure

- Toshiba's most advanced desktop print technology is incorporated into the sleekest case design for ultimate user experience.
- Coming with a new powerful and scalable system architecture the BV410D/BV420D future-prooves your investment.
- With a broad set of standard interfaces and optional Wi-Fi or Bluetooth, the BV410D/BV420D easily integrates into even the most complex IT environments.





The ever-changing workplace

Delivering reliability to meet future challenges

Every business is unique. That's why Toshiba offers the most reliable print solutions that meet all your labeling requirements, day after day. Toshiba barcode printers provide connectivity and solutions to adapt to the needs of an ever-changing workplace.

Toshiba's barcode printers continue to deliver on our promise of Together Information – our commitment to collaborate with clients to provide tailored, cost-effective solutions that meet your evolving workplace needs.

The strong combination of excellent design & advanced connectivity

Toshiba's most advanced desktop printer consists of five different models, all with a small footprint, intelligent design which brings simplicity and efficiency raising the user experience to the next level. Latest connectivity features enable this printer to be integrated into various networks and, thanks to printer language emulations, into almost every print scenario. The robustness of the printer offers high print quality and performance rivalling the majority of mid-ranged printers.



Smooth design yet outstanding

Designed with the user in mind

Ultimate compactness is core design criteria that led to the creation of the BV410D/BV420D desktop printer range, suitable for versatile applications. With its small footprint and clean case these printers suit retail shops, offices or any workplaces where space is a premium.

Usability clear as day

The sleek design of the BV410D/BV420D eliminates all redundant fussiness and concentrates on delivering clarity of operation to the user. The integrated LCD screen of the BV410D provides clear information and notifications that are emphasised by the colour change of the status LEDs. The user can change main settings directly on the printer whereas the remote operator connections allow the full printer setup from afar.

A model to meet every need

With models available in 203 and 300 dpi versions, also available in black or white cabinets, the BV410D/BV420D suits to fit into almost any operating environment. With the addition of a linerless version enabling the printer to print on adhesive labels with no backing paper reducing waste and keeping the working environment safe and clean.

Future-ready operating system

The redesigned OS platform supports multiprinter language emulations, which enables simple integration into complex IT environments. This platform adds not only performance but extends the connectivity and adaptability of the BV410D/BV420D to keep pace with the requirements of an ever-changing workplace.

Speed & efficiency

A series of features makes sure your desktop printer is ready to print labels and receipts quickly and efficiently at the touch of a button. The BV410D/BV420D's productivity is maximised by market leading print speeds of up to 7 inches per second and an advanced CPU which processes your data even quicker. Thanks to the rapid boot-time the printer is ready almost instantly at power-on.

Delivering reliability to meet future challenges

Designed to endure the toughest retail environments the renowned reliability of the BV410D/BV420D printers eliminates almost any downtime – day after day. With built-in AC adapters¹ the Toshiba desktop printers are the perfect fit, ensuring a safe work place.

Key highlights

- Market leading throughput with up to 7 ips
- Compact & sleek design with a small footprint
- Intuitive & clear user experience
- Vast print languages & emulations
- Huge performance & functionality at a truly low total cost of ownership



Specifications

Models

White case Resolution User Interface

Black case Resolution User Interface

Black case linerless cutter Resolution User Interface Cutter

BV410D-GS02 203 dpi (8 dots/mm) 2x LED, 3x key, with LCD

BV410D-TS02

BV420D-TS02

3x LED, 2x key

300 dpi (11.8 dots/mm)

300 dpi (11.8 dots/mm)

2x LED, 3x keys, with LCD

BV420D-GS02 203 dpi (8 dots/mm) 3x LED, 2x key

BV420D-GL02 203 dpi (8 dots/mm) 3x LED, 2x key Integrated linerless cutter

General

Print

Print Method	Direct thermal	
Printhead	Flat head	
Dimensions (W x D x H)	<u>BV410D-GS02/TS02</u> <u>BV420D-GS02/TS02</u> 174 x 218 x 173 mm	<u>BV420D-GL02</u> 174 x 288 x 173 mm
Weight	BV410D-GS02/TS02 BV420D-GS02/TS02 2.0 kg	<u>BV420D-GL02</u> 2.6 kg
Memory	128 MB (FROM), 128 MB (SRAM)	
Operating Temperature / Humidity	BV410D-GS02/TS02 BV420D-GS02/TS02 5 - 40°C (41 - 104°F) / 25 - 85% non-condensing relative humidity (RH)	BV420D-GL02 5 - 35°C (41 - 95°F) / 25 - 85% non-condensing relative humidity (RH)
Storage Temperature / Humidity	-20 - 60°C (-4 - 140°F) / 10 - 90% non-condensing relative humidity (RH)	
Power Supply	AC 100 - 240 V, 50/60 Hz	

Media

Alignment	Centred	
Backing Paper Width	<u>BV410D-GS02/TS02</u> <u>BV420D-GS02/TS02</u> 25.4 - 118 mm	BV420D-GL02 32 - 102 mm
Label Thickness	0.06 - 0.19 mm	
Inner Media Core Diameter	<u>BV410D-GS02/TS02</u> <u>BV420D-GS02/TS02</u> 25.4, 38.1, 42, 76.2 mm	BV420D-GL02
Outer Media Core Diameter	BV410D-GS02/TS02 BV420D-GS02/TS02	BV420D-GL02
Standard Optional	Max. 127 mm Max. 214 mm	Max. 107 mm
Media Format	<u>BV410D-GS02/TS02</u> BV420D-GS02/TS02	BV420D-GL02
	Roll, fanfold	Roll

Software & Connectivity

Emulation	ZPL II, DPL, SBPL
Printer Driver	Windows 10/8.1/8/7 (32/64 bit), Windows Server 2016, Windows Server 2012 R2/Server 2012/Server 2008 R2, SAP
SDK	iOS, Android, Windows, Java
Interface	USB 2.0, Ethernet 10/100 Base T (IPv4 & IPv6), WLAN 802.11a/b/g/n (dual band for 2.4 GHz/5 GHz) ¹⁾²⁾ , Bluetooth V2.1 EDR with MFi certified ¹⁾²⁾ , Serial port ¹⁾
Language Mode	TPCL, Basic Command Interpreter (BCI)
Label Software	BarTender UltraLite (co-packed)

Options

For BV410D/BV420D	Full cutter module ³⁾ , Partial cutter module ³⁾ , Peel-off module ³⁾ , Serial interface board, Wireless LAN module, Bluetooth module, AC adapter cover, External media stand ³⁾
 ¹⁾ Optional ²⁾ Availability varies from cour ³⁾ Not available for BV420D-GI 	· · · · ·





Sensor BV410D-GS02/TS02 BV420D-GL02 BV420D-GS02/TS02 Reflective Reflective, transmissive BV410D/420D-GS02 Max. Print Speed BV410D/420D-TS02 BV420D-GL02 7 ips (177.8 mm/s) 5 ips (127 mm/s) Max. Print Width BV410D/420D-GS02 BV410D/420D-TS02 BV420D-GL02 108 mm 105.7 mm 99 mm **Print Length** 8 - 997 mm Batch 19.4 - 993 mm¹⁾ Cut Peel-off 23.4 - 150.4 mm¹⁾ Barcodes UPC/EAN/JAN, Code 39, Code 93, Code 128, EAN 128, NW7, MSI, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, POSTNET, RM4SCC, KIX Code, Customer Barcode, GS1 DataBar, USPS Intelligent Mail Barcode Data Matrix, PDF 417, MaxiCode, QR Code, 2D Codes Micro PDF 417, Micro QR, GS1 Data Matrix, Aztec Code

Bitmap font, outline font, price font, optional TTF, Fonts writable characters

About Toshiba Tec

Toshiba Tec Corporation is a leading provider of information technology, operating across multiple industries – ranging from retail, education and business services to hospitality and manufacturing. With headquarters in Japan and over 80 subsidiaries worldwide, Toshiba Tec Corporation helps organisations transform the way they create, record, share, manage and display information.

For more information please contact us:

Toshiba Tec Corporation 1-11-1, Osaki, Shinagawa-ku, Tokyo 141-8562, Japan

Website www.toshibatec.com

Together Information is Toshiba's vision for how people and organisations create, record, share, manage and display ideas and data.

It is based on our belief that the most successful organisations are those that communicate information in the most efficient way.

We make that possible through an integrated portfolio of industry-specific solutions, all of which reflect Toshiba's commitment to the future of the planet.

Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation. Copyright ©2020 Toshiba Tec. BR_BV400D_20210325