

# Granit 1911i1D

## Upgradeable Wireless Industrial-Grade Area-Imaging Scanner

The Granit™ 1911i1D wireless industrial-grade area-imaging scanner is designed to withstand the demands of harsh working environments. Designed for real-world reliability, the IP65-rated Granit 1911i1D scanner is built to survive 5,000 1 m (3.3 ft) tumbles and 50 drops to concrete from 2 m (6.5 ft), even at -20°C (-4°F). As a result, businesses can expect to experience minimal device downtime and a lower overall cost of ownership.

The Granit 1911i1D scanner offers omnidirectional scanning of 1D codes for improved efficiency, along with the ability to affordably upgrade the device to 2D scanning as data capture needs evolve.

Powered by sixth-generation Honeywell Adaptus™ imaging technology and its revolutionary decoding architecture, the Granit 1911i1D scanner provides users with the same exceptional barcode reading performance as the best-in-class Xenon™ series area-imaging scanners. From poorly printed and damaged codes to low-density linear codes, the Granit 1911i1D scanner is built to read virtually all 1D and PDF417 barcodes with ease – supporting maximum operator productivity with its enhanced illumination, crisp laser aiming, and extended depth of field.

The Granit 1911i1D scanner also incorporates a Bluetooth® Class 1, v2.1 radio, enabling wireless connectivity and unrestricted movement up to 100 m (300 ft) from the base. Additionally, with the Honeywell Shift-PLUS power management system, users can expect up to 14 hours of battery life, reducing the cost associated with battery backups and replacements. A paging system is also available for added convenience to assist with locating misplaced scanners.



*The Granit 1911i1D wireless area-imaging scanner is optimized for demanding, arm's-length scanning of 1D and PDF417 barcodes, delivering exceptional performance and durability for harsh industrial environments.*

Created specifically for applications in which high-performance scanning is expected and durability is highly valued, the Granit 1911i1D scanner is the optimal solution for businesses operating in unpredictable conditions.

## FEATURES & BENEFITS



The custom-built IP65-rated housing is able to withstand 5,000 1 m (3.3 ft) tumbles and 50 drops from 2 m (6.5 ft) at -20°C (-4°F), reducing service costs and increasing device uptime.



Bluetooth Class 1, v2.1 radio enables movement up to 100 m (300 ft) from the base, and reduces interference with other wireless systems. Up to 7 imagers can communicate with a single base, reducing total cost of ownership.



The Honeywell TotalFreedom™ area-imaging development platform enables the loading and linking of multiple applications to enhance image decoding, data formatting, and image processing – eliminating the need for host system modifications.



The long-lasting Lithium-Ion battery powers up to 50,000 scans per full charge and is removable without tools, ensuring maximum uptime for operations running multiple shifts.



With its extended linear depth of field, the scanner scans out-of-reach items with ease and allows users to scan 20 mil linear codes out to 75 cm (29.5 in).

# Granit 1911i1D Technical Specifications

## WIRELESS

**Radio/Range:** 2.4 GHz to 2.5 GHz (ISM Band)  
Adaptive Frequency Hopping; Bluetooth v2.1: Class 1: 100 m (300 ft) line of sight

**Data Rate (Transmission Rate):** Up to 1 Mbps

**Battery:** 2400 mAh Li-Ion minimum

**Number of Scans:** Up to 50,000 scans per charge

**Expected Hours of Operation:** 14 hours

**Expected Charge Time\*:** 4.5 hours

## MECHANICAL/ELECTRICAL

### Dimensions (L x W x H):

**Scanner:** 133 mm x 75 mm x 195 mm  
(5.2 in x 2.9 in x 7.6 in)

**Charger/Communication Base:** 250 mm x 103 mm x 65 mm (9.9 in x 4.1 in x 2.6 in)

### Weight:

**Scanner:** 390 g (13.8 oz)

**Charger/Communication Base:** 290 g (10.2 oz)

### Operating Power (Charging):

**Scanner:** N/A

**Charger/Communication Base:** 5 W (1A @ 5 V)

### Non-Charging Power:

**Scanner:** N/A

**Charger/Communication Base:** 0.6 W  
(0.12A @ 5 V)

### Host System Interfaces:

**Scanner:** N/A

**Charger/Communication Base:** USB, Keyboard Wedge, RS-232 TTL

## ENVIRONMENTAL

### Operating Temperature\*\*:

**Scanner:** -20°C to 50°C (-4°F to 122°F)

**Charger/Communication Base:** -20°C to 50°C  
(-4°F to 122°F)

### Storage Temperature:

**Scanner:** -40°C to 70°C (-40°F to 158°F)

**Charger/Communication Base:** -40°C to 70°C  
(-40°F to 158°F)

### Humidity:

**Scanner:** Up to 95% relative humidity, non-condensing

**Charger/Communication Base:** Up to 95% relative humidity, non-condensing



## Drop:

**Scanner:** Designed to withstand 50 2 m (6.5 ft) drops to concrete at -20°C (-4°F)

**Charger/Communication Base:** Designed to withstand 50 1.2 m (4 ft) drops to concrete at -20°C (-4°F)

## Tumble:

**Scanner:** 5,000 1 m (3.3 ft) tumbles

**Charger/Communication Base:** 5,000 1 m (3.3 ft) tumbles

## Environmental Sealing:

**Scanner:** IP65

**Charger/Communication Base:** IP51

## Light Levels:

**Scanner:** 0 to 100,000 lux (9,290 foot-candles)

**Charger/Communication Base:** N/A

## ESD:

**Scanner:** ±20 kV air discharge, ±8 kV contact discharge

**Charger/Communication Base:** ±20 kV air discharge, ±8 kV contact discharge

## SCAN PERFORMANCE

**Scan Pattern:** Area Imager (838 x 640 pixel array)

**Motion Tolerance:** Up to 610 cm/s (240 in/s) at 16.5 cm (6.5 in) and 381 cm/s (150 in/s) at 25 cm (10 in) for 13 mil UPC

**Scan Angle:** ER Focus

**Horizontal:** 31.6°

**Vertical:** 24.4°

**Symbol Contrast:** 20% minimum reflectance difference

**Pitch, Skew:** 45°, 65°

**Warranty:** 3-year factory warranty (Note: Battery warranty is 1-year.)

\* Battery charging only occurs between 5°C and 40°C (41°F to 104°F).

\*\* With industrial-grade cable ordered separately.

TYPICAL PERFORMANCE*	EXTENDED RANGE (ER)
<b>NARROW WIDTH</b>	
7.5 mil Code 39	48 mm – 310 mm (1.9 in – 12.2 in)
13 mil UPC	15 mm – 543 mm (0.6 in – 21.4 in)
20 mil Code 39	15 mm – 749 mm (0.6 in – 29.5 in)
6.7 mil PDF417	69 mm – 226 mm (2.7 in – 8.9 in)
Resolution 1D Code 39	5 mil (0.127 mm)

\* Performance may be impacted by barcode quality and environmental conditions.

For a complete listing of all compliance approvals and certifications, please visit [www.honeywellaidc.com/compliance](http://www.honeywellaidc.com/compliance).

For a complete listing of all supported barcode symbologies, please visit [www.honeywellaidc.com/symbologies](http://www.honeywellaidc.com/symbologies).

Adaptus, Granit, TotalFreedom, and Xenon are trademarks or registered trademarks of Honeywell International Inc. in the United States and/or other countries.

Bluetooth is a trademark or registered trademark of Bluetooth SG, Inc. in the United States and/or other countries.

All other trademarks are the property of their respective owners.

## For more information

[www.honeywellaidc.com](http://www.honeywellaidc.com)

## Honeywell Safety and Productivity Solutions

9680 Old Bailes Road

Fort Mill, SC 29707

800-582-4263

[www.honeywell.com](http://www.honeywell.com)